




Natural drying with fresh air. For perfectly dry dishes

The 3000 AirDry Dishwasher maximises drying using natural airflow. The door automatically opens 10 cm in the final stage of the cycle, drying dishes naturally and effectively. Dishes dry 3x better than closed-door systems.

Product Benefits & Features



Open the door to dry dishes

AirDry delivers up to 3x better drying performance when compared to closed-door systems. The door automatically opens at the end of the drying phase and air is circulated inside the machine. Dishes emerge perfectly dry. Every time.



Efficiently clean. In every cycle

The special sensor in our AutoSense program detects how much cleaning your dishes need. Using just the right amount of water, energy and time needed to do the job properly. Meaning dishes are cleaned in the most eco-friendly way possible.



Seamless integration

PerfectFit Sliding Hinge system makes for seamless dishwasher installation. It accommodates all niche machine heights and removes the need to cut the plinth. Fit for any modern kitchen.

- Capacity: 14 Place Settings
- Sensorlogic
- Multi-tab
- Delay Start
- Height Adjustable Upper Basket
- Floor Beam
- Audible Alarm

Product Specification

Series	5000	Door Colour	None
Energy Rating	E	Upper Spray Arm Type	Standard spray arm
Number of Place Settings	14	Lower Spray Arm Type	Standard
Dishwasher Programs	90 Minutes, AUTO Sense, ECO, Machine Care, Quick 30 Minutes	Inlet Pipe Type	Aqua control
Indicators	Rinse aid, Salt, Buzzer, Delay start 3h, Drying phase, Program selected, Beam on floor two coloured, XtraPower, Machine Care	Anti-flood Device Type	Floating switch
Drying System	AirDry Technology	ProdPartCode	B - Open All
Noise Rating (dB)	C	Noise (dB)	46
Dimensions (mm) (HxWxD)	818x596x550	Energy Consumption per 100 wash cycles (kWh)	95
Built-in Dimensions (mm) (HxWxD)	820-900x600x550	Culterly Basket	No
Water Supply	Cold or hot	Cutlery Drawer	Knife rack holder, MaxiFlex Drawer, Removable dividers
Cord Length (m)	1.5		
Inlet Hose Length (cm)	150		
Outlet Hose Length (cm)	150		
Total Electricity Loading (W)	1950		
Wheels/Feet	2 adj feet + 1 front adj rear foot (adj 0 to 8cm)		
Voltage (V)	220-240		
Required Fuse (A)	10		
Frequency (Hz)	50		
Number of Programmes	5		
Number of Temperatures	2		

